OSRAM

LEDinspect Flood 10W

Inspection lights





1000 lm

Bright, white light by high performance

LEDs



Rechargeable battery

Operating time of up to 5 h (high) / up to 10 h (low) / up to 12 h (flashing)



Water- and dirt repellent

Protection against the ingress of particles with $\emptyset \ge 1.0$ mm and against splash water according to IP54 / IK06



Light is versatile

This high-quality inspection light is perfect for professional and private use. For a variety of applications e.g for a wide and large-area lighting of rooms, areas and surfaces. With three light functions - high, low and flashing - 25 LEDs, 10 watts and up to 6000 Kelvin and a rechargeable 3.7 V 4000 mAh lithium battery, this headlight has an operating time of up to 5 h (high) / up to 10 h (low) / up to at 20 h (flashing). With the IP protection class IP54, IK06, this spotlight is protected against the ingress of particles with $\emptyset \ge 1.0$ mm and against splash water. It can also be used as a power bank as 2 USB connections are integrated. This LED flooder is easy to transport, has a non-slip and dirt-repellent surface, contains an integrated angle stand & magnets for hands-free work and easy attachment, and is therefore ideal as a work lamp for manual activities, car repairs, renovation and painting work. OSRAM also offers a 2-year warranty on this product*

Product datasheet

Technical data

Product information

| Order reference | LEDIL FLOOD 10W | |
|---|--|--|
| Application (Category and Product specific) | LED inspection lights for personal use | |


Electrical data

| Nominal wattage | 10.00 W |
|-----------------|---------|
| Nominal voltage | 3.7 V |

Photometrical data

| Color temperature | 6000 К |
|-------------------|------------|
| Luminous flux | 10W/500 lm |
| Light color LED | White |

Dimensions & weight



| Product weight | 710.00 g |
|----------------|----------|
| Length | 161.0 mm |
| Width | 176.0 mm |
| Height | 59.0 mm |

Colors & materials

| Base color | Black |
|------------|-------|
| | |

Lifespan

| Guarantee | 2 years |
|-----------|---------|
|-----------|---------|

Additional product data

| Type of Battery | rechargeable |
|-----------------|--------------|
| | |

Product datasheet

| | , |
|------------------------------|------|
| Number of included batteries | n.a. |

Capabilities

| Technology | LED ¹⁾ |
|------------|-------------------|

 $^{^{1)}}$ Light-emitting diode lamp

Certificates & standards

| Type of protection | IP54 |
|--------------------|------|
| Standards | CE |

Country specific categorizations

| Order reference | LEDIL FLOOD 10W |
|-----------------|-----------------|
| | |

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|---------------------|---------------------------------|--------------------------------------|-----------------------|--------------|
| 4062172092326 | INSPECTION LAMP | Folding carton box 1 | - x - x - | | |
| 4062172125871 | INSPECTION LAMP | Shipping carton box | 382 mm x 215 mm x 200 mm | 16.43 dm ³ | 5003.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

| File |
|---|
| Movie application OSRAM LEDinspect Flooder Trailer (EN) |
| 360 Degree Image TL1207 |

Application advice:

For more detailed application information and graphics please see product datasheet.

Disclaimer:

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

*for precise conditions please refer to:

www.osram.com/am-guarantee

Application advice

Product datasheet

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

