



IP65



50,000
HOURS

5

YEARS'
WARRANTY

3000K
4000K
5700K

CCT
SELECTABLE



NEXT DAY
DELIVERY

COMMERCIAL RANGE



VENTURE
LIGHTING



YEARS'
WARRANTY



Interior and Exterior
options available.



3000K

4000K

5700K

CCT
SELECTABLE

The **IP65 rated** Bamburgh bulkhead can be used **indoors and out** with **four trim levels** to suit **every occasion**.

Customise your project even further with **integral 3 hour emergency and microwave sensor options**.

BAMBURGH

BULKHEAD

Order Code: AMY005-KITBG-EM


Photometric Data	
Lumens	870
Emergency Mode Lumens	227
Emergency Duration (Hrs)	3
Colour Rendering Index (CRI)	80-89
Adjustable CCT	Positions
LPW (lm/W)	95
Colour Temperature (K)	3000-5700
SDCM	SDCM6
Light Distribution	Symmetric
Lens / Reflector	Diffuser lens/optic/panel



Life Data		
Rated Life (Hrs)	Ta = 25C	
	50000	
Lumen Maintenance (Hrs)	Ta = 25C	
	B50	B10
	L70	-
	L80	-
	L90	50000

Electrical Data	
Microwave Sensor	No
Integral Emergency Inverter	Yes
Battery Type	LiFePO4
Light Sensor	No
PIR Sensor	No
Input Current (mA)	70-70
No. Per B16 Breaker	48
No. Per C16 Breaker	64
Input (W)	14
Input (V)±10%	200-240
Voltage Type	AC
Power Factor	0.9
Energy Efficiency Class (EEC)	A++, A+, A (LED)
Electrical Class	II
Type of Wiring	Suitable for through wiring
Non-dimmable	Yes
Emergency Lighting	Yes

Physical Data	
Degree of Protection (IP)	IP65
Housing Colour	Black
Housing Material	Plastic
Height/Depth (mm)	90
Diameter (mm)	350
Suitable for surface mounting	Yes
Lamp Type	LED exchangeable
Cover Material	Plastic- opal
Impact Strength	IK06



Order Code: AMY005-KITBG-EM

Environmental Data

Ambient Rated Temperature Range (°C)	0-45
--------------------------------------	------

Logistical Data

Packaging Length (mm)	340
Packaging Width (mm)	340
Packaging Height (mm)	350
Carton Length (mm)	590
Carton Width (mm)	350
Carton Height (mm)	35
Carton Weight (kg)	9
Quantity per Carton	6