Protect 001 LED



IK10

IP65

LED

-(tw)-

2,5mm²

CE



Protect - a robust and vandal resistant IP65 fitting with LED and sensor

Description

Protect 001 is a quality fitting in a circular shape (001) made of high pressure die-cast aluminium. Diffuser in UV- and vandal resistant polycarbonate. The front ring is fixed with 4 torx screws in stainless steel which are given a Delta seal treatment. IP65 class I. A number plate is available as accessories. The plate is fixed together with the fitting from behind.

Application areas

P-house, facades, entrances, stairs, pedestrian areas, underpasses and tunnels.

Mounting

for professionals

Direct in ceiling or on wall. The fittings can also be mounted on the Arc pole.

lights

Installation

The fitting is prepared both for open and hidden installation. Push in terminal block 3x2x2,5 mm² with through-wiring possibilities.

LED module


Colour temperature30Effect fitting12Luminous flux fitting50LifetimeL7

3000K - 4000K 12W 505 Im L70B50 50.000 t

Additional

The sensibility is adjusted on the microwave sensor. Likewise the hold time (exposure time after detected movement) might be adjusted (5 sek - 25 min). The sensor has also a setting for a twilight function (2 - 30 lux). Radar can also be used as Master for other fittings.

201		ł
	0	
25	Δ	



House number plate

White	Black	Alu	Туре	Light source	NB!	
108501 111858 114983 111594 111867	108692 111859 117549 111595 111868	108693 111860 117852 111596 111869	Protect 001 LED Protect 001 LED Radar Protect 001 LED Radar MinMax Protect 001 LED Protect 001 LED Radar	LED 12W 840 LED 12W 840 LED 12W 840 + LED 1W E14 LED 12W 830 LED 12W 830	A microwave sensor detect all forms of movement, not only from people and animals. This means that the sensor might detect movements for instance from branches or	
Accessor 105289	119246 ries: 111437	119245	Protect 001 LED Radar MinMax Number plate	LED 12W 830 + LED 1W E14	leaves. Please allow for this when installing the fitting to awoid unwanted functions.	

