

LED A60 E27 12-60V AC/DC 7W 3000K

Bailey nr.: 143115



BEE LED GLS A60 E27 7W 3000K Opal 550lm Low voltage 12V-24V-28V-42V-48V-50V-60V AC/DC 170D 60x110mm LED-lamp

The wide voltage range makes this LED lamp very versatile.

| General properties | |
|--|---------------------------|
| EAN-code | 8714681431153 |
| Product series | BaiSpecial LED |
| Product Type | A60 Low voltage |
| Specifications | |
| Nominal voltage | 12 60 V |
| Voltage type | AC/DC |
| Nominal current | |
| Power factor | 0.6 |
| Lamp power | 7 7 W |
| Luminous flux | 550 550 lm |
| Rated luminous flux according to IEC 62722-2-1 | |
| Lamp efficacy | 78.57 lm/W |
| Luminous intensity | |
| Colour rendering index CRI | 80-89 |
| Lamp shape | Pear-shape |
| Type of glass/cover | Opal |
| Colour of light according to EN 12464-1 | Neutral white 3300-5300 K |
| Socket | E27 |
| Colour | White |
| Colour of light | 830 830 |
| Colour temperature | 3000 3000 K |
| Colour housing | White |
| Beam angle | 160 ° |
| Colour consistency (McAdam ellipse) | SDCM5 |
| Dimmable | No |
| Diameter | 60 mm |
| Length | 110 mm |
| Degree of protection (IP) | IP20 |
| Energy Efficiency Index (EEI) | |
| Min. number of switching cycles | 50000 |
| Weighted energy consumption in 1000 hours | 7 kWh |
| Average nominal lifespan | 25000 h |

