

LED Corn HOL E40 100V-240V 27W 6500K

Bailey nr.: 80100036290



BAI LED Corn HOL E40 100-240V 27W 6500K 4100lm 330D 93x206mm IP64 120V 130V 230V Alt HME HQL HPL HSE HST SON NAV DISCONNECT BAL-LAST

The LED Corn HOL with no less than 150lm/W is the ideal retrofit replacement for, among others, energy-saving lamps, incandescent lamps, mercury vapor lamps and metal halide lamps in both indoor and outdoor applications such as: street lighting and parking lot lighting, indoor applications where there is a high ceiling or a large space needs to be lit. (warehouse, church, classroom, hall, etc.). Installation: disconnect the ballast before use. Burning position: universal. Ambient temperature range: -25°C to +40°C.

General properties	
EAN-code	8714681362907
Product series	LED Corn
Product Type	HOL
Specifications	
Nominal voltage	100 240 V
Voltage type	AC
Nominal current	300 300 mA
Power factor	0.9
Lamp power	27 27 W
Luminous flux	4100 4100 lm
Rated luminous flux according to IEC 62722-2-1	
Lamp efficacy	152 lm/W
Luminous intensity	
Colour rendering index CRI	80-89
Lamp shape	Tube, single-ended
Type of glass/cover	Clear
Colour of light according to EN 12464-1	Daylight white >5300 K
Socket	E40
Colour	White
Colour of light	865 865
Colour temperature	6500 6500 K
Colour housing	White
Beam angle	330 °
Colour consistency (McAdam ellipse)	Other
Dimmable	No
Diameter	93 mm
Length	206 mm
Degree of protection (IP)	IP64
Energy Efficiency Index (EEI)	0.09
Min. number of switching cycles	15000
Weighted energy consumption in 1000 hours	27 kWh
Average nominal lifespan	50000 h

