

LED PL G24d TC-D 8W 840 CL

Bailey nr.: 80100036395

BAI LED PL G24d 2-pins TC-D 8W 4000K Clear 590lm 100V-240V 120D 46x158mm Rotating cap LED-lamp Alt PLC Dulux D



The LED PL G24d (2-pin) TC-D lamps with rotating base are replacements for the commonly used compact fluorescent lamps without an integrated ballast. PL stands for PubLic as these lamps are mainly used in wall and ceiling luminaires in public areas, offices, shops and restaurants. Installation: Disconnect the ballast before use. Ambient temperature range: -20°C to +40°C.

General properties	
EAN-code	8714681363959
Product series	LED PL
Product Type	G24d 2P
Specifications	
Nominal voltage	100 240 V
Voltage type	AC
Nominal current	90 90 mA
Power factor	0.9
Lamp power	8 8 W
Luminous flux	590 590 lm
Rated luminous flux according to IEC 62722-2-1	
Lamp efficacy	74 lm/W
Luminous intensity	
Colour rendering index CRI	80-89
Lamp shape	Tube, single-ended
Type of glass/cover	Clear
Colour of light according to EN 12464-1	Neutral white 3300-5300 K
Socket	G24d
Colour	White
Colour of light	840 840
Colour temperature	4000 4000 K
Colour housing	White
Beam angle	120 °
Colour consistency (McAdam ellipse)	SDCM6
Dimmable	No
Diameter	46 mm
Length	158 mm
Degree of protection (IP)	IP40
Energy Efficiency Index (EEI)	0.16
Min. number of switching cycles	15000
Weighted energy consumption in 1000 hours	8 kWh
Average nominal lifespan	50000 h

