

LED Floodlight HQ Black 100-240V 30W 6500K

Bailey nr.: 90500034704



BAI LED Floodlight HQ 30W 6500K 3000lm 100-240V DC IP65 IK08 Alu housing black 120D 2m cable

The Floodlight is also called a spotlight or construction lamp. The Led version consumes little power and lasts a long time so that they are more durable than the traditional predecessors. Can be mounted on both wall and ceiling. The housing is made of cast aluminum. Comes with 2m connection cable. Suitable for ambient temperatures from -10°C to +40°C. Refer to specifications and warranty for installation.

General properties	
EAN-code	8714681347041
Product series	LED Floodlight
Product Type	HQ
Specifications	
Adjustability	Swivelling
With movement sensor	No
With light sensor	No
With light source	Yes
Lamp holder	None
Material housing	Aluminium
Surface protection	Other
Colour housing	Black
Material cover	Glass transparent
Nominal voltage (V)	100 240 V
Voltage type	AC
LED nominal current at constant current	
Dimmable	No
Light sharing	Symmetric
Beamangle	Extreme wide beam >80°
Rated life time L70/B10 at 25 °C	
Rated life time L70/B50 at 25 °C	45000 h
Rated life time L80/B10 at 25 °C	
Rated life time L80/B50 at 25 °C	
Rated life time L90/B10 at 25 °C	
Rated life time L90/B50 at 25 °C	
Degree of protection (IP)	IP65
Impact strength	IK08
Protection class	I
Rated ambient temperature	-10 40 °C
Max. system power (W)	30 W
Colour of light	Other
Colour temperature (K)	6500 6500 K
Colour rendering index CRI	60-69

Specifications	
Luminous flux (lm)	3000 3000 lm
Lamp efficacy (lm/w)	100 lm/W
Power factor	
Width	225 mm
Height/depth	125 mm
Length	185 mm
Outer diameter	
Built-in height/depth	
Built-in diameter	

Bailey 90500034704

This luminaire contains built-in LED lamps.

A++
A+
A
B
C
D
E

} LED

The lamps cannot be changed in the luminaire.

874/2012